

Orca 50 Lite

UHF Handheld Reader Data Terminal





1. Advantages



High Performance Computing Platform

Powerful hardware configurations to ensure applications like massive data collection, 3D real-time display can be operated smoothly.



Android 6.0

Android 6.0 OS, keep optimizing and updating.



Top Class Materials

Cast Aluminium, PC+ABS (SABIC) body with 1.1mm thickness tempered glass offer excellent strength + heat dissipation + electromagnetic shielding features. Soft material around the handle offers a comfortable grip.



Industrial-grade components + super long life cycle

Industrial-grade and military-grade components ensure stable operation in harsh environments. Over ten years of supply can be offered, which provides guarantee for the long term projects.



Ultra Long Operating Time

Pistol style hot-swappable battery system makes backup battery more convenient to be restored, so that the operating time is unlimited.(extra batteries are available)



High-end UHF RFID Engine

Equipped with self-developed Rodinbell M-2600 module based on Impinj R2000 chip, offering the best performance and excellent multi-tag identification ability in the industry.



Outstanding Industrial Design

The idea was inspired by orca, and each single detail has been well refined. The appearance is compact, elegant and balanced, which makes the product eye-catching and impressive.



Excellent Mechanical Protection

Safety drop height 1.6m. With IP64 protection grade to resist dusts and splashes effectively.

Shanghai Jiayulian Technology Co.,Ltd | www.jyl-world.com | info@jyl-world.com | +86 178 8798 3711

The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.

2. Electrical Parameters



Mechanical parame	eters	Data Collections	
Materials Dimensions Weight	Cast Aluminium+PC case 167*82*129mm Grip 111*38*47mm 615g (battery included)	1D Barcode Optional	Motorola EM1350 UPC/EA Symbol SE955N/Code128/ Code39/Code93/Code11/ Interleaved 2 of 5/ Discrete 2 of 5/ Chinese 2 of 5/Codabar/MSI/ RSS.etc.
System Characteris Operating System CPU GPU RAM +ROM	Android 6.0 Quad-core Cortex-A17 / 1.8 GHz ARM Mali-T764/High performance 3D engine 2G+32G	2D Barcode Optional	Zebra SE4750, NLS EM3396, EM3296 Data matrix / QR Code / PDF417 / US Planet / UK Postal, etc.
LCD Touch Screen	4G+64G	UHF RFID Engine Protocol	Rodinbell M-2600 module based on Impinj Indy R2000 chip EPC Global UHF Class 1 Gen 2 /
Hotswapping Battery Buttons Power / Volume	Pistol style hotswapping battery system 3 ALPS buttons/ Operating force 2.5N / Operating life 1 million cycles	Frequency Output Power Peak Inventory Speed	ISO 18000-6C / ISO 18000-6B 902-928MHz , 865- 868MHz 0~33dBm > 500 tags /s
Scan Trigger Power	OMRON button / Operating force 1.27N/ Operating life 10 million cycles 6,000mAh chargeable li-polymer battery	UHF Antenna Read Distance Supported Regions	4dBi air dielectric antenna > 10m US, Canada and other regions following
Card Slots USB Interface	Nano SIM card slot*1 / TF card slot*1 Micro USB / MOLEX connector /Operating life 10,000 cycles		US FCC Europe and other regions following ETSI EN 302 208
Audio Vibration Charge Indicator	Large speaker stereo system Button style / 10mm diameter Bicolor LED		China Korea Malaysia

Wireless Communications

WIFI	IEEE802.11b / g / n	
Bluetooth	Bluetooth 4.0	
4G	Supported Optiona	

Application Environment

Operating Temp	-20°- +60°
Storage Temp	-30°- +70°
Humidity	5%RH - 95%RH (non -condensing)
Protection Grade	IP64
Safety Drop Height	1.6m / 5.25ft



13 megapixels/ automatic focus/ flashlight

Global positioning system

GPS&GLONASS

Accessories





Data cable



Hanging Lace

Shanghai Jiayulian Technology Co.,Ltd | www.jyl-world.com | info@jyl-world.com | +86 178 8798 3711

The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.