

RFID Token



Application:

- Automatic production management
- Asset tracking
- Device embedded

Key Features

- Strong lamination housing
- Anti-collision and harsh resistant
- Low cost
- Additional ABS + Epoxy for waterproof

Tag Spec.:

| | | | |
|------------|--|-----------------------|-------------------------------|
| Material: | ABS, PC | IP Class | IP68 |
| Size: | 22/25/30/35/40/50/52mm 12/20/25/30/35/40/50/52mm 20/25/30/35/40/50/52mm or customized | Resistance: | Waterproof Harsh resistant |
| Thickness: | 2.3/3/4.8/7.8mm for optional | Operating Temperature | -40 to 70℃ |
| | | Storage Temperature: | -45 to 80℃ |

Optional Craft:

| | |
|---------------------|---|
| Coding: | Chip Encoding |
| Custom logo: | Silkscreen printing, Laser engrave |
| ID Number Printing: | Laser engrave |
| On Metal: | Anti-Metal Ferrite Layer optional |
| Adhesive: | Ordinary Adhesive sticker, 3M Adhesive Layer Optional |
| Warranty: | 1 year |


Self-adhesive Tag



White Tag



Tag with Epoxy



Logo Pre-printed Tag



The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.