

## JYL-NMT4219



## **Highlights:**

layer stoped the interference of the metal. The tag is fixed by screw, it is very steady in industrial environment. To handle very harsh outdoor environment, the tag is filed with epoxy, so it is completely resist water and dust.

On Metal tag is designed for industrial applications on metal, The inner antimetal

## Tag Spec.:

• •			
Housing	Nylon/ABS material + Filling epoxy	Operating Frequency:	LF, HF, UHF for optionl
Dimension:	42 x 19.5 x 5.3mm	Approx Weight:	18g / 5g
Thickness:	5.3mm / 8mm	Color:	Black / Yellow
Store temperature:	-30°C ~ +75°C	Protection:	IP68
Working temperature:	-25°C ~ +60°C	Resistance:	Harsh out door environment, Water/dust proof

## **Optional :**

Coding:	Chip Encoding
Customized Logo Printing:	Laser engrave
ID Number Printing:	Laser engrave
Data Retention	10 years
Warranty:	1 year



The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.

Shanghai Jiayulian Technology Co.,Ltd | T:+86 186 0166 4655 / 178 8798 3711 | info@jyl-world.com | www.jyl-world.com