

RFID Keyfob JYL-GP01

RFID Glassfiber Pear Keyfob is a popular keyfob which with very light body and their thickness is only 1.6mm . Its constructed of sturdy glassfiber making it tougher and durable enough . People like them very much and widely use for security and access control .

CHIP Available Frequency: LF HF UHF Dual

Product Specification:

Material	Glassfiber
Dimension	L45 x W30 x T0.9mm
IP Class	IP68
Operating Temp.	- 25°C to 100°C
Storage Temp.	- 25°C to 120°C
Net Weight	Approx 3.2g/pc
Packing	100pcs/Bag,1000pcs/Carton
Colors	Black
MOQ	500pcs for Black Color, 2000pcs for Red and White Color



Personalisation Options:

- ☆ Pad Printing
- ☆ Photo Printing
- ☆ Full-color Printing
- ☆ Laser Engraved Number
- ☆ Chip Encoding
- ☆ Rings or Thread is optional

Applications:

- ☆ Access Control
- ☆ Time Attendance
- ☆ Loyalty System
- ☆ Payment NFC System
- ☆ Health Clubs
- ☆ Leisure Areas

Chip Available:

	18000-part2	EM4200, TK4100, etc.
125KHz	ISO11784/785	T5577, EM4305, Hitag1, Hitag2, Hitag S256, etc.
	ISO15693	ICODE SLI, Tag-it 2048, etc.
13.56Mhz	ISO18082	NTAG210, NTAG212, NTAG213, NTAG215, NTAG216, Topaz512, etc.
	ISO14443A	MIFARE Classic [®] , MIFARE Ultralight [®] , MIFARE [®] DESFire [®] EV1, MIFARE Plus [®] , Fudan FM11RF08, etc.
860Mhz-960Mhz	ISO/IEC 18000-6C EPC Class1 Gen2	UCODE, MONZA, HIGGS, etc.

Other IC types availabel on request !

The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.