

RFID Keyfob KA03

RFID keyfob is the extension products of normal ISO card, which is designed for easy carry by person. JYL-Tech RFID keyfobs combine the RFID technology with good looking and practical keyfob housings. They can easily be fitted to a normal metal key ring.

CHIP Available Frequency:

LF HF UHF

Product Specification:

Material	ABS
Dimension	41*30*T5.3mm
IP Class	IP67
Operating Temp.	- 25°C to 55°C
Storage Temp.	- 25°C to 75°C
Net Weight	Approx 4g/pc
Packing	100pcs/Bag,1000pcs/Carton
Colors	Gray, Black, Blue, Red, White, Green, Yellow, etc.
MOQ	2000PCS





Personalisation Options:

\precsim Pad Printing	\precsim Photo Printing	$\stackrel{\wedge}{\asymp}$ Full-color Printing	ightarrow Laser Engraved Number	$\stackrel{\wedge}{ ightarrow}$ Chip Encoding
$\stackrel{\scriptstyle <}{\sim}$ Rings or Thread is optional				

Applications:

 \Rightarrow Access Control \Rightarrow Time Attendance \Rightarrow Loyalty System \Rightarrow Payment NFC System \Rightarrow Health Clubs \Rightarrow Leisure Areas

Chip Available:

	18000-part2	EM4200, TK4100, etc.
125KHz	ISO11784/785	T5577, EM4305, Hitag1, Hitag2, Hitag S256, etc.
	ISO15693	ICODE SLI, Tag-it 2048, etc.
13.56Mhz	ISO18082	NTAG210, NTAG212, NTAG213, NTAG215, NTAG216, Topaz512, etc.
	ISO14443A	MIFARE Classic [®] , MIFARE Ultralight [®] , MIFARE [®] DESFire [®] EV1, MIFARE Plus [®] , Fudan FM11RF08, etc.
860Mhz-960Mhz	ISO/IEC 18000-6C EPC Class1 Gen2	UCODE, MONZA, HIGGS, etc.

Other IC types availabel on request !

The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.

Shanghai Jiayulian Technology Co.,Ltd | T:+86 186 0166 4655 / 178 8798 3711 | info@jyl-world.com | www.jyl-world.com