

# **RFID Keyfob KA04**

RFID keyfob is the extension products of normal ISO card, which is designed for easy carry by person. JYL-Tech RFID keyfobs combine the RFID technology with good looking and practical keyfob housings. They can easily be fitted to a normal metal key ring.

CHIP Available Frequency:

LF HF UHF Dual

## **Product Specification:**

Material ABS or Nylon (+ Epoxy Pading Option)

Dimension L52 x W32 x T5.5mm

**IP Class** IP68

Operating Temp. - 25°C to 65°C - 25°C to 75°C Storage Temp. Net Weight Approx 5g/pc

**Packing** 100pcs/Bag,1000pcs/Carton

Gray, Black, Blue, Red, White, Green, Yellow, etc. Colors

☆ Time Attendance

MOQ 500PCS

### **Personalisation Options:**

☆ Pad Printing ☆ Photo Printing ☆ Laser Engraved Number ☆ Full-color Printing

☆ Rings or Thread is optional ☆ Chip Encoding

## **Applications:**

☆ Access Control

☆ Loyalty System ☆ Payment NFC System

#### **Chip Available:**

18000-part2 EM4200, TK4100, etc.

125KHz ISO11784/785 T5577, EM4305, Hitag1, Hitag2, Hitag S256, etc.

> ISO15693 ICODE SLI, Tag-it 2048, etc.

ISO18082 13.56Mhz NTAG210, NTAG212, NTAG213, NTAG215, NTAG216, Topaz512, etc.

> ISO14443A MIFARE Classic \*, MIFARE Ultralight\*, MIFARE\*DESFire\*EV1, MIFARE Plus\*, Fudan FM11RF08, etc.

ISO/IEC 18000-6C 860Mhz-960Mhz UCODE, MONZA, HIGGS, etc. EPC Class1 Gen2

Other IC types availabel on request!

The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.

ABS



