

RFID Keyfob KA09

RFID keyfob is the extension products of normal ISO card, which is designed for easy carry by person. JYL-Tech RFID keyfobs combine the RFID technology with good looking and practical keyfob housings. They can easily be fitted to a normal metal key ring.

CHIP Available Frequency:



Product Specification:

Material ABS

Dimension 36*42*T6.3mm

IP Class IP68

Operating Temp. - 25°C to 55°C

Storage Temp. - 25°C to 75°C

Net Weight Approx 4g/pc

Packing 100pcs/Bag,1000pcs/Carton

Colors Gray, Black, Blue, Red, White, Green, Yellow, etc.

MOQ 500PCS



☆ Rings or Thread is optional

Applications:

☆ Access Control ☆ Time Attendance ☆ Loyalty System ☆ Payment NFC System ☆ Health Clubs ☆ Leisure Areas

Chip Available:

18000-part2 EM4200, TK4100, etc.

125KHz ISO11784/785 T5577, EM4305, Hitag1, Hitag2, Hitag S256, etc.

ISO15693 ICODE SLI, Tag-it 2048, etc.

13.56Mhz ISO18082 NTAG210, NTAG212, NTAG213, NTAG215, NTAG216, Topaz512, etc.

ISO14443A MIFARE Classic *, MIFARE Ultralight*, MIFARE*DESFire*EV1, MIFARE Plus*, Fudan FM11RF08, etc.

860Mhz-960Mhz ISO/IEC 18000-6C

EPC Class1 Gen2 UCODE, MONZA, HIGGS, etc.

Other IC types availabel on request!

The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.

