

# **RFID Keyfob KA15**

RFID keyfob is the extension products of normal ISO card, which is designed for easy carry by person. JYL-Tech RFID keyfobs combine the RFID technology with good looking and practical keyfob housings. They can easily be fitted to a normal metal key ring.

CHIP Available Frequency:

quency: LF HF UHF Dual

## **Product Specification:**

Material	ABS
Dimension	39.5*31*T5.6mm
IP Class	IP68
Operating Temp.	- 25°C to 55°C
Storage Temp.	- 25°C to 75°C
Net Weight	Approx 8.5g/pc
Packing	100pcs/Bag,1000pcs/Carton
Colors	Gray, black, Blue, Red, White, Green, Yellow, etc.
MOQ	500PCS





### **Personalisation Options:**

$\precsim$ Pad Printing	$\stackrel{\wedge}{\asymp}$ Photo Printing	$\precsim$ Full-color Printing	$\stackrel{\scriptstyle \wedge}{ m $\!$	ightarrow Chip Encoding
$ m \AA$ Rings or Threa	d is optional			

#### **Applications:**

🕸 Access Control	☆ Time Attendance	🕁 Loyalty System	☆ Payment NFC System	🕁 Health Clubs	🛱 Leisure Areas
------------------	-------------------	------------------	----------------------	----------------	-----------------

# **Chip Available:**

	18000-part2	EM4200, TK4100, etc.
125KHz	ISO11784/785	T5577, EM4305, Hitag1, Hitag2, Hitag S256, etc.
	ISO15693	ICODE SLI, Tag-it 2048, etc.
13.56Mhz	ISO18082	NTAG210, NTAG212, NTAG213, NTAG215, NTAG216, Topaz512, etc.
	ISO14443A	MIFARE Classic <sup>®</sup> , MIFARE Ultralight <sup>®</sup> , MIFARE <sup>®</sup> DESFire <sup>®</sup> EV1, MIFARE Plus <sup>®</sup> , Fudan FM11RF08, etc.
860Mhz-960Mhz	ISO/IEC 18000-6C EPC Class1 Gen2	UCODE, MONZA, HIGGS, etc.

#### Other IC types availabel on request !

The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.

Shanghai Jiayulian Technology Co.,Ltd | T:+86 186 0166 4655 / 178 8798 3711 | info@jyl-world.com | www.jyl-world.com